

WEATHERPROOF BOXES

Weatherproof Boxes - 1 Gang

Depth: 2"

Length: 4-9/16" Width: 2-13/16"

Copper-free die-cast aluminum

UL File No. E476800









FSB50-3 FSB75-3

FSB50-4 FSB75-4

FSB50-5 FSB75-5

FSB50-5X FSB75-5X

Applications:

- · For use in branch circuit wiring in wet, damp or dry locations
- · May be used as a weatherproof junction box or as a housing for receptacles and switches

Cat. No.	Hub Size	No. of Holes	Hole Location	Color	Standard Pkg
FSB50-3	1/2"	3	top, bottom, back	Gray	50
FSB75-3	3/4"	3	top, bottom, back	Gray	50
FSB50-4	1/2"	4	1 top, 2 bottom, 1 back	Gray	50
FSB75-4	3/4"	4	1 top, 2 bottom, 1 back	Gray	50
FSB50-5	1/2"	5	2 top, 2 bottom, 1 back	Gray	50
FSB75-5	3/4"	5	2 top, 2 bottom, 1 back	Gray	50
FSB50-5X	1/2"	5	1 at each side	Gray	50
FSB75-5X	3/4"	5	1 at each side	Gray	50

^{*}Boxes supplied with 2 closure plugs, 1 grounding screw, and 2 mounting lugs with self-tapping screws.

Flanged Extension Ring - 1 Gang

Depth: 1-1/2" Length: 5-3/16" Width: 3-15/32" Die Cast Aluminum



Application:

• Extension adaptors provide means for adding additional cubic capacity.

Cat. No.	Hub Size	No. of Holes	Hole Location	Color	Standard Pkg
EXF50-4	1/2"	4	2 top, 2 bottom	Gray	20
EXF75-4	3/4"	4	2 top, 2 bottom	Gray	20

Weatherproof Blank Cover - 1 Gang

Dimension: 2-13/16" x 4-9/16"

Material: Steel **Application:**

Where weatherproof protection is required while an outlet is in use.

Cat. No.	Description	Color	Standard Pkg
1BC	1-Gang cover with gasket	Gray	100

