


## PVC Cable Glands

### Features:

- Rubber Gasket: Nitrile Rubber (NBR)
- Protection Grade: IP68
- Ambient temperature stick -40°C to 100°C, for short time 120°C,
- Dynamic state: -20°C to 80°C, short time 100°C
- Color: Black RAL9005



**METRIC TYPE**  
Material: Nylon



**PG TYPE**  
Material: Nylon PA, UL94-V0



**NPT TYPE**  
Material: Nylon

ITEM CODE	CABLE RANGE
I-MCG-CGA-00001	3-6.5mm
I-MCG-CGA-00002	5-10mm
I-MCG-CGA-00003	10-14mm
I-MCG-CGA-00004	13-18mm
I-MCG-CGA-00005	18-25mm
I-MCG-CGA-00006	22-32mm
I-MCG-CGA-00007	32-38mm
I-MCG-CGA-00008	37-44mm

ITEM CODE	CABLE RANGE
I-MCG-CGA-00009	3-6.5mm
I-MCG-CGA-00010	4-8mm
I-MCG-CGA-00011	5-10mm
I-MCG-CGA-00013	6-12mm
I-MCG-CGA-00021	10-14mm
I-MCG-CGA-00014	13-18mm
I-MCG-CGA-00015	18-25mm
I-MCG-CGA-00016	22-32mm
I-MCG-CGA-00017	32-38mm
I-MCG-CGA-00018	37-44mm

ITEM CODE	CABLE RANGE
I-MCG-CGA-00012	6-12mm
I-MCG-CGA-00019	13-18mm
I-MCG-CGA-00020	18-25mm

## Steel Conduit Locknut

Material: Steel

Application: To secure threaded conduit or connector to a box or an enclosure



CATALOG NO.	TRADE SIZE	DIMENSION (IN)	
		A	B
LNS050	1/2"Ø	1.087	0.122
LNS075	3/4"Ø	1.358	0.142
LNS100	1"Ø	1.661	0.157
LNS125	1-1/4"Ø	2.047	0.157
LNS150	1-1/2"Ø	2.366	0.181
LNS200	2"Ø	2.929	0.187
LNS250	2-1/2"Ø	3.449	0.248
LNS300	3"Ø	4.189	0.232
LNS350	3-1/2"Ø	4.646	0.283
LNS400	4"Ø	5.146	0.240