

**LIQUIDTIGHT FLEXIBLE CONDUIT**

**ULTRA TUFF, TYPE EF**

**Features:**

- Zinc galvanized steel strip, interlocked
- Water-proof, oil resistant
- Temperature rating: -20°C ~ +80°C
- PVC jacket in grey color
- IP rating: IP65

**Application:**

- Provides mechanical protection for conductors in
- oily and harsh chemical environments
  - commercial and high-rise buildings
  - industrial applications
  - machineries / motor controls
  - for installation where flexibility is needed or where vibration and/or movement is present



Trade Size		Inside Diameter Ø		Outside Diameter Ø		Bending Radius	Length per pack
in.	mm	Min (mm)	Max (mm)	Min (mm)	Max (mm)	mm	
1/2	16	15.80	16.30	20.80	21.30	93	200
3/4	21	20.80	21.30	25.20	26.70	118	200
1	27	26.40	27.00	32.80	33.40	175	200
1-1/4	35	35.00	35.80	41.40	42.20	213	100
1-1/2	41	40.00	40.60	47.40	48.30	239	50
2	53	51.30	51.90	59.30	60.30	293	50
2-1/2	63	63.00	63.63	72.10	73.00	381	20
3	78	78.00	78.70	87.90	88.00	454	20
4	103	101.60	102.60	113.20	114.30	620	20